

SPECIFICATIONS

Programmable DC Power Supply

MODEL : EX600 - 10



ODA
TECHNOLOGIES

www.odacore.com

Parameter		Specifications			
Output rating(@0°C ~ 40°C)	Voltage	0 to 600.0	Maximum 630.0		
	Current	0 to 10.0	Maximum 10.5		
Output WATT			6.6 KW		
Programming Accuracy (@25°C ±5°C)±(%of output + offset)	Voltage	0.1% + 900.0mV			
	Current	0.1% + 30.0mA			
Readback Accuracy (@25°C ±5°C)±(%of output + offset)	Voltage	0.1% + 600.0mV			
	Current	0.1% + 20.0mA			
Ripple and Noise(20Hz to 20MHz)		≤ 240mVrms			
Load Regulation (with V-Sensing)		≤ 600 mV			
Line Regulation (with V-Sensing)		≤ 600 mV			
Resolution	Programming/Readback	≤ 10mV / ≤ 0.2mA			
	Display Meter	100mV / 10mA			
Temperature Coefficient	Voltage	≤ 120.0mV			
After a 30-minute warm-up	Current	≤ 3.0mA			
Stability ±(%of output + offset)	Voltage	≤ 300.0mV			
After a 1 hour warm-up	Current	≤ 5.0mA			
Voltage Programming Speed (10%~90% of output voltage)	Half load	Rising time	≤ 300ms		
		Falling time	≤ 300ms		
Remote Sensing Capability	Voltage Drop	Up to 2.5V per each lead			
	Load Regulation	Add 5 mV to spec for each 1-volt change in the + output lead due to load current changes			
	Load Voltage	Subtract voltage drop in load leads from specified output voltage rating.			
OVP and OCP Accuracy ±(%of output + offset)	OVP	1% + 6.0V			
	OCP	1% + 1.0A			
	Activation Time	< 80ms when maximum output rating			
Output Voltage Overshoot & Undershoot	Power Switch ON/OFF	No overshoot, undershoot : ≤ -0.8V			
	Voltage Output Setting	No overshoot, No undershoot			
Remote Interface	RS232C , RS485 , USB Standard (TCP/IP Option)				
Programming Language	SCPI(Standard Commands for Programmable Instruments)				
Command Processing Time(average)	Apply	Setting	20ms		
		Query	32ms		
	Output Setting	Voltage & Current Setting	15ms		
		Voltage & Current Query	32ms		
	Measurement	Voltage & Current Query	32ms		
		Setting & Query	< 35ms		
State Storage Memory	Ten user-configurable(voltage,current,protection level)stored states				
Operation Temperature	0°C ~ 40°C for full rated output. At higher temperatures the output current is derated linearly to 50% at 55°C maximum temperature				
Cooling	Isolation DC FAN				
Output Terminal Isolated (maximum, from chassis ground)	±60 Vdc when connecting shorting conductors without insulation to the (+)output to the (+)sense and the (-)output and the (-)sense terminals				
AC Input Ratings	Standard	single phase 220V ± 10% 50~60Hz			
	Option	3-phase 4-wire system(R,S,T,N,G) ± 10% 50~60Hz			
Calibration Interval	Precision	6 month			
	Recommended	1 year			
Dimensions (19" Standard)	426(W) * 176(H) * 550(D)				
Maximum Input Power(full load)	7.6 KW				
Weight	Net weight	26.5kg			
	Gross weight	28kg			

*상기모델은 사용자 Application에 최적화하기위해 예고없이 사양변경될 수 있으므로 구입전 확인하시기 바랍니다.