

SPECIFICATIONS

Programmable DC Power Supply

MODEL : OPS-5001



ODA

TECHNOLOGIES
www.odacore.com

| Parameter | | Specifications | |
|---|--|--|------------|
| Output rating(@0°C ~ 40°C) | Voltage | 0 to 500 | |
| | Current | 0 to 1 | |
| Output WATT | | 500.0W | |
| Programming Accuracy (@25°C ±5°C)±(%of output + offset) | Voltage | 0.15% + 110mV | |
| | Current | 0.15% + 5mA | |
| Readback Accuracy (@25°C ±5°C)±(%of output + offset) | Voltage | 0.08% + 80mV | |
| | Current | 0.08% + 3mA | |
| Ripple and Noise(20Hz to 20MHz) | Voltage | ≤ 0.005% mV_{rms} | |
| | Current | ≤ 3mA rms | |
| Load Regulation (with V-Sensing) | Voltage | ≤ 4mV | |
| | Current | ≤ 500 μ A | |
| Line Regulation (with V-Sensing) | Voltage | 1mV | |
| | Current | 500 μ A | |
| Resolution | Programming/Readback | ≤ 5mV / ≤ 10 μ A | |
| | Display Meter | 100mV / 100 μ A | |
| Temperature Coefficient ±(%of output + offset) After a 30-minute warm-up | Voltage | 0.01% + 50mV | |
| | Current | 0.02% + 3mA | |
| Stability ±(%of output + offset) After a 1 hour warm-up | Voltage | 0.02% + 50mV | |
| | Current | 0.1% + 1mA | |
| Transient Response Time | | Less than 50 μ s for output to recover to within 15mV following a change in output current from full load to half load or vice versa | |
| Voltage Programming Speed | No load | Rising time | ≤ 7.5V/ms |
| | | Falling time | ≤ 0.2V/ms |
| | Half load | Rising time | ≤ 3.25V/ms |
| | | Falling time | ≤ 1V/ms |
| Remote Sensing Capability | Voltage Drop | Up to 1V per each lead | |
| | Load Regulation | Add 5 mV to spec for each 1-volt change in the + output lead due to load current changes | |
| | Load Voltage | Subtract voltage drop in load leads from specified output voltage rating. | |
| OVP and OCP Accuracy ±(%of output + offset) | OVP | 5% + 5V | |
| | OCP | 5% + 0.1A | |
| | Activation Time | < 80ms when maximum output rating | |
| Output Voltage Overshoot & Undershoot | Power Switch ON/OFF | No overshoot, undershoot : ≤ -0.8V | |
| | Voltage Output Setting | No overshoot, No undershoot | |
| Remote Interface | | GPIB(IEEE-488.2) Option , RS232C Standard | |
| Programming Language | | SCPI(Standard Commands for Programmable Instruments) | |
| Command Processing Time(average) | Apply | Setting | 20ms |
| | | Query | 32ms |
| | Output Setting | Voltage & Current Setting | 15ms |
| | | Voltage & Current Query | 32ms |
| | Measurement | Voltage & Current Query | 32ms |
| The Other | Setting & Query | < 35ms | |
| State Storage Memory | | Ten user-configurable(voltage,current,OVP & OCP level)stored states | |
| Cycling Mode | Step(Voltage,Current, Slope & Delay time) | Maximum 100 steps | |
| | Slope time | 0sec ~ 86,400sec (24 hours) | |
| | Delay time | 100ms ~ 86,400sec(24 hours) | |
| | Repeat | Maximum 15million times | |
| Operation Temperature | | 0°C ~ 40°C for full rated output. At higher temperatures the output current is derated linearly to 50% at 55°C maximum temperature | |
| Cooling | | Isolation AC & DC FAN | |
| Output Terminal Isolated (maximum, from chassis ground) | | ±60 Vdc when connecting shorting conductors without insulation to the (+)output to the (+)sense and the (-)output and the (-)sense terminals | |
| AC Input Ratings | Standard | 220V ± 10% 50~60Hz | |
| | | 110V ± 10% 50~60Hz | |
| | Option | 115V ± 10% 50~60Hz | |
| | | 230V ± 10% 50~60Hz | |
| Calibration Interval | Precision | 6 month | |
| | Recommended | 1 year | |
| Dimensions | Standard | 426mm(W) * 177mm(H) * 505mm(D) 19-inch 4U Standard Size | |
| Maximum Input Power(full load) | | 1.3KW | |
| Weight | Net weight | 19kg | |
| | Gross weight | 20.5kg | |

*상기모델은 사용자 Application에 최적화하기위해 예고없이 사양변경될 수 있으므로 구입전 확인하시기 바랍니다.